



MUR2050CT~MUR20600CT

ULTRAFAST RECOVERY RECTIFIERS

VOLTAGE 50 to 600 Volts **CURRENT** 20 Amperes


TO-220AB Unit : inch(mm)

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound.
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency.
- Low forward voltage, high current capability
- High surge capacity.
- Ultra fast recovery times, high voltage.

MECHANICAL DATA

- Case: TO-220AB full molded plastic package
- Terminals: Lead solderable per MIL-STD-750, Method 2026
- Polarity: As marked.
- Standard packaging: Any
- Weight: 0.0655 ounces, 1.859 grams.



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

| PARAMETER | SYMBOL | MUR2050CT | MUR20100CT | MUR20200CT | MUR20300CT | MUR20400CT | MUR20600CT | UNITS |
|---|-----------------|-------------|------------|------------|------------|------------|------------|-----------------------------|
| Maximum Recurrent Peak Reverse Voltage | V_{RRM} | 50 | 100 | 200 | 300 | 400 | 600 | V |
| Maximum RMS Voltage | V_{RMS} | 35 | 70 | 140 | 210 | 280 | 420 | V |
| Maximum DC Blocking Voltage | V_{DC} | 50 | 100 | 200 | 300 | 400 | 600 | V |
| Maximum Average Forward Current lead length at $T_C = 100^\circ\text{C}$ | $I_{F(AV)}$ | 20 | | | | | | A |
| Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load (JEDEC method) | I_{FSM} | 150 | | | | | | A |
| Maximum Forward Voltage at 10A | V_F | 1 | | 1.3 | | 1.7 | | V |
| Maximum DC Reverse Current at Rated DC Blocking Voltage $T_J=25^\circ\text{C}$ $T_J=125^\circ\text{C}$ | I_R | 1 500 | | | | | | μA |
| Typical Junction Capacitance (Note 1) | C_J | 200 | | | | | | pF |
| Maximum Reverse Recovery Time (Note 2) | t_{rr} | 35 | | | | | 50 | ns |
| Typical Thermal Resistance (Note 3) | $R_{\theta JC}$ | 2 | | | | | | $^\circ\text{C} / \text{W}$ |
| Operating Junction and Storage Temperature Range | T_J, T_{STG} | -65 to +150 | | | | | | $^\circ\text{C}$ |

NOTES:

1. Measured at 1 MHz and applied reverse voltage of 4.0 VDC.
2. Reverse Recovery Test Conditions: $I_F=0.5\text{A}$, $I_R=1\text{A}$, $I_{rr}=0.25\text{A}$.
3. Thermal resistance from Junction to ambient and from junction to lead

MUR2050CT~MUR20600CT

RATING AND CHARACTERISTIC CURVES




Fig.1 FORWARD CURRENT DERATING CURVE




Fig.2 TYPICAL JUNCTION CAPACITANCES




Fig.3 FORWARD CHARACTERISTICS




Fig.4 TYPICAL REVERSE CHARACTERISTICS




Fig.5 PEAK FORWARD SURGE CURRENT